



隔离环形变压器

TOROIDAL POWER Isolation Transformers

Input: 220/240V
Output: 220/240V

型号	功率	电压调整率	效率	外观尺寸		重量	产品认证
PRODUCT MODEL	RATED POWER	VOLTAGE REGULATION	EFFICIENCY	DIMENSIONS		WEIGHT	APPROVAL
	VA	V	%	D	H	Kg	
TI-100	100	9.5%	89%	105	50	1.56	CE, AU, CQC
TI-250	250	7.5%	92%	125	65	3.4	CE, AU, CQC
TI-500	500	6.5%	93%	135	75	5	CE, AU, CQC
TI-750	750	6.0%	94%	150	80	7.2	CE, AU, CQC
TI-1000	1000	5.5%	94%	155	80	8.8	CE, AU, CQC
TI-1500	1500	4.8%	95%	175	80	12.2	CE, AU, CQC
TI-2000	2000	4.5%	95%	175	115	14.5	CE, AU, CQC
TI-2500	2500	4.0%	95%	185	115	16.8	CE, AU, CQC
TI-3600	3600	3.5%	96%	210	120	20	CE, AU, CQC
TI-5000	5000	3.2%	96%	225	125	24.8	CE, AU, CQC
TI-6000	6000	3.2%	96%	245	135	28.6	CE, AU, CQC